













 <p><b>TYPE SOG</b></p>	 <p><b>TYPE DOG</b></p>	 <p><b>TYPE TOG</b></p>	 <p><b>TYPE QOG</b></p>
<b>END FITTINGS</b>		<b>ADJUSTABLE SINGLE CHAIN SLING</b>	
 <p><b>MASTER LINK (O)</b></p>	 <p><b>SLING HOOK (S)</b></p>	 <p><b>GRAB HOOK (G)</b></p>	 <p><b>TYPE ASOS</b></p>
<p>THESE END FITTINGS AVAILABLE ON ALL TYPES OF CHAIN SLINGS.</p>			<p>AVAILABLE IN SINGLE, DOUBLE, TRIPLE AND QUADUPLE</p>

### WORKING LOAD LIMIT - 4 TO 1 DESIGN FACTOR

ALLOY CHAIN SIZE (IN.)	SINGLE LEG (S)	DOUBLE LEG (D)				(T) TRIPLE AND QUAD (Q)		
	90° 	60° 	45° 	30° 	60° 	45° 	30° 	
7/32	2100	3600	3000	2100	5450	4450	3150	
1/4 (9/32)	3500	6100	4900	3500	9100	7400	5200	
5/16	4500	7800	6350	4500	11700	9600	6700	
3/8	7100	12300	10000	7100	18400	15100	10600	
1/2	12000	20800	17000	12000	31200	25500	18000	
5/8	18100	31300	25600	18100	47000	38400	27100	
3/4	28300	49000	40000	28300	73500	60000	42400	
7/8	34200	59200	48400	34200	88900	72500	51300	
1	47700	82600	67400	47700	123900	101200	71500	
1-1/4	72300	125200	102200	72300	187800	153400	108400	

THE DESIGN FACTOR OF 4 TO 1 ON ALLOY CHAIN AGREES WITH THE DESIGN FACTOR USED BY THE INTERNATIONAL STANDARDS ORGANIZATION (I.S.O.) AND ANSI B30.9 IS THE PREFERRED SET OF WORKING LOAD LIMIT VALUES TO THE USED.

**WARNING** DO NOT EXCEED RATED CAPACITIES

### F.O.B. WAREHOUSE

NYLON & POLYESTER WEBBING SLINGS • JACOB & SOLAS LADDERS • MANILA & SYNTHETIC ROPE & SPLICING • CARGO & SAFETY NETS  
POLYESTER ROUND SLINGS • DIRT SLINGS • TIEDOWN STRAPS & EQUIPMENT • MARINE & INDUSTRIAL RIGGING EQUIPMENT