


TYPE 1 TRIANGLE AND CHOKER



TYPE 1 (TCA(S)) TRIANGLE AND CHOKER SLINGS - STEEL OR FORGED ALUMINUM CHOKER HARDWARE PROVIDES FOR SMOOTH, SNUG CHOKE HITCHING. THEY CAN ALSO BE USED IN VERTICAL AND BASKET HITCHES.

TYPE 2 (TAA(S)) TRIANGLE AND TRIANGLE SLINGS - STEEL OR FORGED ALUMINUM BASKET HARDWARE IS ATTACHED TO EACH END OF THE SLING. FOR USE IN VERTICAL AND BASKET HITCHES ONLY.

UNI LINKS CAN BE USED ON 2", 3", AND 4" WEBBING. REPLACES TRIANGLE CHOKER HARDWARE AND CHOKES FROM EITHER END OF SLING.



FOR TYPE 1, TYPE 2, AND UNI LINKS, END FITTINGS CAN INCREASE THE LIFE OF THE SLING SINCE THE EYES ARE A MAJOR WEARPOINT ON THE SLINGS.

TYPE 2 TRIANGLE AND TRIANGLE



TYPE 3 FLAT EYE



TYPE 3 (EEF) FLAT EYE SLINGS ARE VERY POPULAR AND CAN BE USED IN ALL THREE TYPES OF HITCHES. THEY ARE EASIER TO REMOVE FROM BENEATH THE LOAD AFTER THE LOAD IS IN PLACE. UNLESS TYPE 4 IS REQUESTED, TYPE 3 WILL BE SUPPLIED AS THE STANDARD EE SLING.

TYPE 4 (EET) TWISTED EYE SLINGS ARE SIMILAR TO TYPE 3, EXCEPT THE EYES ARE TURNED 90° TO FORM A BETTER CHOKER HITCH. THIS TYPE OF EYE ALSO NESTS TOGETHER BETTER ON THE CRANE HOOK WHEN USED IN A BASKET HITCH.

TYPE 4 TWISTED EYE



	RATED CAPACITY IN LBS.				
	TYPE 1	TYPE 2	VERTICAL	CHOKER	BASKET
	TCA(S)	TTA(S)			
ONE PLY	1-602		2200	1760	4400
	1-603		3300	2640	6600
	1-604		4400	3520	8800
	1-605		5500	4400	11000
	1-606		6600	5280	13200
TWO PLY	2-602		4400	3520	8800
	2-603		6600	5280	13200
	2-604		8200	6560	16400
	2-605		10200	8160	20400
	2-606		12300	9840	24600

3 AND 4 PLY HARDWARE SLINGS ARE AVAILABLE UPON REQUEST. CANNOT BE USED WITH CHOKER HITCH.

NOTE: ANGLES MAY AFFECT CAPACITY OF SLING. SEE SLING ANGLE CHART.

ALL OF THESE SLINGS ARE DESIGNED FOR LIGHT DUTY WORK AND LESS FREQUENT SERVICE. LIGHT DUTY WEB FEATURES A RED CORE YARN SYSTEM. APPROXIMATELY 1/8" THICK. AVAILABLE IN NYLON ONLY.

WARNING DO NOT EXCEED RATED CAPACITIES

	RATED CAPACITY IN LBS.				
	TYPE 3	TYPE 4	VERTICAL	CHOKER	BASKET
	EEF	EET			
ONE PLY	1-601		1100	880	2200
	1-601.5		1600	1280	3200
	1-602		2200	1760	4400
	1-603		3300	2640	6600
	1-604		4400	3520	8800
	1-605		5500	4400	11000
TWO PLY	2-601		2200	1760	4400
	2-601.5		3300	2640	6600
	2-602		4400	3520	8800
	2-603		6600	5280	13200
	2-604		8200	6560	16400
	2-605		10200	8160	20400
THREE PLY	3-601		3300	2640	6600
	3-601.5		4900	3920	9800
	3-602		6600	5280	13200
	3-603		9900	7920	19800
	3-604		12000	9600	24000
	3-605		15000	12000	30000
FOUR PLY	4-601		4400	3520	8800
	4-601.5		6600	5280	13200
	4-602		8800	7040	17600
	4-603		13300	10640	26600
	4-604		16400	13120	32800
	4-605		20400	16320	40800
4-606		24600	19680	49200	

TYPES 3 AND 4 EYES ARE TAPERED AT 3" AND WIDER UNLESS OTHERWISE ORDERED. EYE LENGTH AND WIDTH VARY WITH SLING WIDTH AND NUMBER OF WEBBING PLYS.

NOTE: ANGLES MAY AFFECT CAPACITY OF SLING. SEE SLING ANGLE CHART.

F.O.B. WAREHOUSE

NYLON & POLYESTER WEBBING SLINGS • JACOB & SOLAS LADDERS • MANILA & SYNTHETIC ROPE & SPLICING • CARGO & SAFETY NETS
POLYESTER ROUND SLINGS • DIRT SLINGS • TIEDOWN STRAPS & EQUIPMENT • MARINE & INDUSTRIAL RIGGING EQUIPMENT