


TYPE 6 REVERSED EYE



TYPE 7 FLAT EYE



TYPE 8 WIDE BODY BASKET






TYPE 6 (RE) REVERSED EYES SLINGS WILL OUT-PERFORM ALL OTHER SLING TYPES WHEN CONDITIONS ARE CONTINUOUS AND ABUSIVE. PROTECTIVE WEBBING COVERS BOTH SIDES OF THE SLING BODY AND SLING EYES. THE REVERSED EYE SLINGS HAS EYES THAT ARE 90° TO THE SLING BODY; THIS EYE TYPE RESULTS IN SNUG CHOKE HITCHES.


TYPE 7 (FE) FLAT EYE SLINGS ARE CONSTRUCTED FROM THE SAME MATERIALS AS THE TYPE 6. THE FABRIC IS TURNED 180° FORMING AN EYE WHICH IS IN THE SAME PLANE AS THE SLING BODY. THIS EYE DESIGN PERMITS EASIER REMOVAL OF THE SLING FROM UNDER THE LOAD, ONCE IT HAS BEEN SET.

BOTH TYPE 6 AND TYPE 7 EYE SLINGS CAN BE USED IN CHOKER, VERTICAL, OR BASKET HITCHES.

TYPE 8 (WBB) WIDE BODY BASKET SLINGS ARE DESIGNED FOR USE IN BASKET HITCH WHERE A WIDE SLING IS NEEDED FOR LOAD STABILITY AND WHERE WIDTH IS REQUIRED FOR PROPER HANDLING OF FRAGILE OR HIGHLY FINISHED SURFACES. EYES OF SLINGS ARE TAPERED TO FIT ON HOIST OR CRANE HOOKS AND ARE REINFORCED TO PROVIDE INCREASED DURABILITY.

FOR USE IN BASKET CONFIGURATION ONLY.

	RATED CAPACITY IN LBS.				
			 VERTICAL	 CHOKER	 BASKET
	TYPE 6 RE	TYPE 7 FE			
ONE PLY	1-602		2200	1760	4400
	1-902		3200	2560	6400
	1-603		3200	2560	6400
	1-903		4600	3680	9200
	1-604		4400	3520	8800
	1-904		6200	4960	12400
	1-606		6600	5280	13200
	1-906		9400	7520	18800
TWO PLY	2-602		4400	3520	8800
	2-902		6200	4960	12400
	2-603		6600	5280	13200
	2-903		9200	7360	18400
	2-604		8800	7040	17600
	2-904		12400	9920	24800
	2-606		13200	10560	26400
	2-906		17600	14080	35200

	RATED CAPACITY IN LBS.			
	TYPE 8 WBB	 BASKET	EYE LENGTH L (INCHES)	EYE WIDTH W (INCHES)
ONE PLY	1-606	13200	12	1-1/2
	1-906	18800	12	1-1/2
	1-608	17600	12	2
	1-908	24800	12	2
	1-610	22000	15	1-3/4
	1-910	31200	15	1-3/4
	1-612	26400	15	2
	1-912	37200	15	2
	1-916	51200	18	3
	1-920	64000	24	3-1/2
TWO PLY	1-924	76000	24	4
	2-606	26400	15	1-1/2
	2-906	35200	15	1-1/2
	2-608	32800	15	2
	2-908	44000	15	2
	2-610	40800	18	2-1/2
	2-910	54800	18	2-1/2
	2-612	49200	18	3
	2-912	66000	18	3
	2-916	82000	24	4
2-920	96000	24	5	
2-924	106000	24	6	

3 AND 4 PLY AVAILABLE UPON REQUEST.

NOTE: ANGLES MAY AFFECT CAPACITY OF SLING. SEE SLING ANGLE CHART.

3 PLY WEIGHTS ARE AVAILABLE UPON REQUEST.

NOTE: ANGLES MAY AFFECT CAPACITY OF SLING. SEE SLING ANGLE CHART.

WARNING DO NOT EXCEED RATED CAPACITIES

F.O.B. WAREHOUSE

NYLON & POLYESTER WEBBING SLINGS • JACOB & SOLAS LADDERS • MANILA & SYNTHETIC ROPE & SPLICING • CARGO & SAFETY NETS
POLYESTER ROUND SLINGS • DIRT SLINGS • TIEDOWN STRAPS & EQUIPMENT • MARINE & INDUSTRIAL RIGGING EQUIPMENT